

## THICK-WALLED PC FLAT DRIPLINE

# AmmonDrip PC, CNL & PC AS



**Innovative, pressure-compensating (PC) dripline with special anti-syphon (AS) and compensating non-leakage (CNL) models. Cascade labyrinth feature incorporated in all drippers**

### APPLICATIONS

- Ideal solution for irrigation in topographically challenging terrain, and where long laterals are required
- CNL option for pulse irrigation of orchards, open field crops and greenhouses
- Subsurface Drip Irrigation (SDI), for accurate irrigation of orchards, open field crops and greenhouses

### STRUCTURE AND FEATURES

- Pressure-compensating (PC) enabling water application accuracy at variable topography and the installation of long laterals
- Efficient self-cleaning turbulence provided by the Cascade labyrinth
- Hydrodynamic dripper design ensures continuous flushing of sediments and small dirt particles
- Low CV for maximal uniformity
- Weir structure improves root intrusion resistance and sand suction
- 3D water inlet structure improves clog resistance
- High-quality silicon diaphragm
- Both carton and coil package options are available (see packing and shipping table)
- Colored cap facilitates easy identification of dripper models

### SPECIAL MODELS

- CNL: Pressure-compensating non-leakage design reduces lateral filling time and facilitates pulse irrigation
- PC AS: Pressure compensating anti-syphon design prevents suction at draining stage. Suitable for subsurface drip irrigation

**AmmonDrip PC**



0.5, 1.1, 1.6, 2.0, 2.2, 3.8 l/h

**AmmonDrip CNL**



0.5, 1.1, 1.6, 2.0, 2.2, 3.8 l/h

**AmmonDrip PC AS**



0.5, 1.1, 1.6, 2.0, 2.2, 3.8 l/h



### TECHNICAL DATA


- Flow rates: 0.5, 1.1, 1.6, 2.0, 2.2, 3.8 l/h
- CNL: Opening pressure - 1 bar  
Closing pressure - 0.2 bar
- AS: Opening pressure - 0.5 bar
- Pressure regulating range:  
PC & AS models - 0.5-4.0 bar  
PC CNL - 1.0-4.0 bar
- Recommended filtration: 130 micron (120 mesh)

## THICK-WALLED PC FLAT DRIPLINE

# AmmonDrip PC, CNL & PC AS

### TECHNICAL DATA

Nominal diameter (mm)	Wall thickness		OD (mm)	ID (mm)	Maximum Pressure (bar)	KD	Connector type	
	(mm)	(mil)					Barb	Tape
16	0.63	25	15.16	13.9	2.5	0.92	●	
	0.90	35	15.70	13.9	3.0	0.92	●	
	1.00	39	15.90	13.9	3.5	0.92	●	
	1.15	45	16.20	13.9	3.5	0.92	●	
17	0.63	25	16.90	15.6	2.5	0.75		●
	0.90	35	16.20	14.4	3.0	0.75	●	
	1.00	39	16.40	14.4	3.0	0.75	●	
	1.20	47	17.00	14.4	3.5	0.75	●	
20	1.00	39	19.70	17.70	3.0	0.65	●	
	1.20	47	20.10	17.70	3.5	0.65	●	
23	1.00	39	22.80	20.8	3.0	0.14		●



### AMMONDRIP PACKAGING AND SHIPPING

#### Carton spools

Nominal diameter (mm)	Wall thickness (mm)	Standard coil length (m)	Coils per 20 ft. container	Coils per 40 ft. container	Coils per 40 ft. HC container
16	0.63	600	320	640	720
	0.90	400	320	640	720
	1.00	400	320	640	720
17	0.63	600	320	640	720
	0.90	400	320	640	720
	1.00	400	320	640	720
20	0.90	300	320	640	720
	1.00	300	320	640	720
23	1.00	300	320	640	720



#### Coils

Nominal diameter (mm)	Wall thickness (mm)	Standard coil length (m)	Coils per 20 ft. container	Coils per 40 ft. container	Coils per 40 ft. HC container
16	0.90	500	150	320	360
	1.00	500	150	320	360
	1.15	500	150	320	360
17	0.90	500	150	320	360
	1.00	500	150	320	360
	1.20	500	150	320	360
20	1.00	300	150	345	365
	1.20	300	150	345	365



\* Dripper spacing can affect coil length.

Available also in brown, white, purple or any other color for a minimum order of 40K m

## THICK-WALLED PC FLAT DRIPLINE

**AmmonDrip 16mm****HEAD LOSS (m) IN RELATION TO LATERAL LENGTH (m), DRIPPER FLOW RATE AND SPACING (cm)**

AmmonDrip 16mm 0.5-l/h W.T 0.9-1.15 mm ID 13.9								AmmonDrip 16, 1.1l/h, W.T 0.9-1.15mm, ID 13.9								AmmonDrip 16, 2.0l/h, W.T 0.9-1.15mm, ID 13.9											
Dripper spacing (cm)								Dripper spacing (cm)								Dripper spacing (cm)											
Lateral length(m)	20	30	40	50	60	70	100	Lateral length(m)	20	30	40	50	60	70	100	Lateral length(m)	20	30	40	50	60	70	100				
20								20	0.2	0.1					20	0.3	0.1	0.1									
40	0.3	0.1	0.1					40	0.9	0.4	0.2	0.1	0.1	0.1	40	1.8	0.7	0.4	0.2	0.1	0.1	0.1					
60	0.9	0.3	0.2	0.1	0.1			60	2.8	1.1	0.6	0.3	0.2	0.2	60	5.2	2.1	1.1	0.6	0.4	0.3	0.1					
80	1.9	0.7	0.4	0.2	0.1	0.1		80	6	2.3	1.2	0.7	0.5	0.4	80	11.4	4.5	2.3	1.4	1	0.7	0.3					
100	3.4	1.3	0.7	0.4	0.3	0.2	0.1	100	11	4.3	2.2	1.4	0.9	0.6	100	20.8	8.2	4.3	2.6	1.7	1.2	0.6					
120	5.5	2.2	1.1	0.7	0.5	0.3	0.1	120	18	7.1	3.7	2.2	1.5	1.1	120	35	13.5	7	4.3	2.9	2.1	1					
140	8.4	3.3	1.7	1	0.7	0.5	0.2	140		10.7	5.6	3.4	2.3	1.6	140		20.4	10.7	6.5	4.4	3.1	1.5					
160	12.1	4.7	2.4	1.5	1	0.7	0.3	160		15.4	8	4.9	3.3	2.4	160		15.4	9.4	6.4	4.6	2.2						
180	16.6	6.4	3.3	2	1.4	1	0.5	180		21.2	11.1	6.8	4.6	3.3	180		21.2	13	8.8	6.4	3						
200		8.6	4.4	2.7	1.8	1.3	0.6	200		14.8	9	6.1	4	2.1	200			17.4	11.8	8.4	4						
220		11.1	5.8	3.5	2.3	1.7	0.8	220		19.2	11.7	7.9	5.7	2.7	220			22.6	15.3	11	5.3						
240		14	7.3	4.4	3	2.1	1	240		24.3	14.9	10.1	7.2	3.4	240				19.5	14	6.7						
260		17.5	9.1	5.5	3.7	2.7	1.2	260			18.5	12.5	9	4.3	260				24.3	17.5	8.3						
280			11.1	6.8	4.5	3.3	1.5	280			22.7	15.3	11.1	5.2	280				21.5	10.2							
300			13.4	8.2	5.5	3.9	1.9	300				18.6	13.4	6.3	300				25.9	12.4							
320			16.1	9.8	6.6	4.7	2.2	320				22.2	16	7.6	320					14.8							
340			19	11.5	7.7	5.5	2.6	340					18.9	9	340				17.5								
360				13.5	9	6.5	3.1	360					22.1	10.5	360				20.6								
380				15.6	10.5	7.5	3.6	380					25.6	12.2	380												
400					18	12.1	8.7	4.1	400						14.1	400											
420						13.8	10	4.7	420						16.1	420											
440							15.8	11.3	5.3	440						18.4	440										
460								17.8	12.8	6	460						20.8	460									
480									20	14.4	6.8	480						23.4	480								
500										16.1	7.6	500							16.1	500							
AmmonDrip 16, 2.2l/h, W.T 0.9-1.15mm, ID 13.9								Dripper spacing (cm)								Dripper spacing (cm)											
Lateral length(m)	20	30	40	50	60	70	100	Lateral length(m)	20	30	40	50	60	70	100	Lateral length(m)	20	30	40	50	60	70	100				
20	0.5	0.2	0.1	0.1				20	1.2	0.5	0.3	0.1	0.1	0.1	20	2.2	0.9	0.4	0.2	0.1	0.1	0.1					
40	3	1.2	0.6	0.4	0.3	0.2	0.1	40	7.7	3.0	1.6	1.0	0.7	0.5	0.2	40	22.9	9.2	4.8	2.9	2.0	1.4	0.7				
60	9	3.6	1.9	1.1	0.7	0.5	0.3	60	19.6	7.7	4.0	2.5	1.7	1.2	0.6	60	19.9	10.4	6.4	4.4	3.2	2.1	1.5				
80								80								80											
100								100								100											
120								120								120											
140								140								140											
160								160								160											
180								180								180											
200								200								200											
220								220								220											
240								240								240											
260								260								260											
280								280								280											
300								300								300											
320								320								320											
340								340								340											
360								360								360											
380								380								380											
400								400								400											
420								420								420											
440								440								440											
460								460								460											
480								480								480											
500								500								500											
AmmonDrip 16, 3.8 l/h, 0.9-1.15mm, ID 13.9								Dripper spacing (cm)								Dripper spacing (cm)											
Lateral length(m)	20	30	40	50	60	70	100	Lateral length(m)	20	30	40	50	60	70	100	Lateral length(m)	20	30	40	50	60	70	100				
20	1.2	0.5	0.3	0.1	0.1	0.1	0.1	20	7.7	3.0	1.6	1.0	0.7	0.5	0.2	20	22.9	9.2	4.8	2.9	2.0	1.4	0.7				
40	3	1.2	0.6	0.4	0.3	0.2	0.1	40	19.6	7.7	4.0	2.5	1.7	1.2	0.6	40	19.9	10.4	6.4	4.4	3.2	2.1	1.5				
60	9	3.6	1.9	1.1	0.7	0.5	0.3	60	14.2	7.4	4.5	3.1	2.2	1.1	0.6	60	23.4	12.2	7.5	5.1	3.6	2.1	1.5				
80								80								80											
100								100								100											
120								120								120											
140								140								140											
160								160								160											
180								180								180											
200								200								200											
220								220								220											
240								240								240											
260								260								260											

## THICK-WALLED PC FLAT DRIPLINE

# AmmonDrip 17mm - W.T 0.63mm



### HEAD LOSS (m) IN RELATION TO LATERAL LENGTH (m), DRIPPER FLOW RATE AND SPACING (cm)

AmmonDrip-17mm 0.5 l/h PC W.T 0.63 mm ID 15.6								AmmonDrip 17, 1.1l/h, W.T 0.63mm, ID 15.6								AmmonDrip 17, 2.0l/h, W.T 0.63mm, ID 15.6								
Dripper spacing (cm)								Dripper spacing (cm)								Dripper spacing (cm)								
Lateral length(m)	20	30	40	50	60	70	100	Lateral length(m)	20	30	40	50	60	70	100	Lateral length(m)	20	30	40	50	60	70	100	
40	0.2	0.1						20	0.1	0.1	0.1	0.1	0.1	0.1	0.1	20	0.2	0.1	0.1	0.1	0.1	0.1	0.1	
60	0.6	0.2	0.1	0.1				40	0.6	0.3	0.2	0.1	0.1	0.1	0.1	40	1.1	0.5	0.3	0.2	0.1	0.1	0.1	
80	1.3	0.5	0.3	0.2	0.1	0.1		60	1.8	0.7	0.4	0.3	0.2	0.2	0.1	60	3.6	1.3	0.7	0.4	0.3	0.2	0.1	
100	2.3	0.9	0.5	0.3	0.2	0.1	0.1	80	3.8	1.5	0.8	0.5	0.4	0.3	0.2	80	6.9	2.8	1.5	0.9	0.6	0.5	0.2	
120	3.6	1.4	0.7	0.4	0.3	0.2	0.1	100	6.8	2.7	1.4	0.9	0.6	0.5	0.2	100	12.4	5	2.7	1.6	1.1	0.8	0.4	
140	5.4	2.1	1.1	0.7	0.5	0.3	0.1	120	10.9	4.4	2.3	1.4	1	0.7	0.4	120	20.1	8.1	4.3	2.6	1.8	1.3	0.6	
160	7.7	3	1.6	1	0.6	0.5	0.2	140	16.4	6.6	3.5	2.1	1.5	1.1	0.5	140	12.2	6.5	4	2.7	2	0.9		
180	10.5	4.1	2.2	1.3	0.9	0.6	0.3	160	9.4	5	3	2.1	1.5	0.7		160	17.4	9.3	5.7	3.9	2.8	1.3		
200	13.8	5.5	2.8	1.7	1.2	0.8	0.4	180	12.8	6.8	4.2	2.8	2	1		180	12.7	7.8	5.3	3.8	1.8			
220	7	3.7	2.2	1.5	1.1	0.5		200	17	9	5.5	3.8	2.7	1.3		200	16.9	10.4	7.1	5.1	2.4			
240	8.8	4.6	2.8	1.9	1.4	0.6		220	11.6	7.1	4.9	3.5	1.7			220	13.4	9.2	6.6	3.1				
260	10.9	5.7	3.5	2.4	1.7	0.8		240	14.7	9	6.1	4.4	2.1			240	17	11.6	8.4	4				
280	13.3	7	4.3	2.9	2.1	1		260	18.2	11.2	7.6	5.5	2.6			260		14.4	10.4	5				
300		8.4	5.1	3.5	2.5	1.2		280		13.6	9.3	6.7	3.2			280		17.6	12.7	6.1				
320		10	6.1	4.1	2.9	1.4		300		16.4	11.2	8.1	3.8			300			15.4	7.3				
340		11.7	7.2	4.8	3.5	1.6		320		19.6	13.3	9.6	4.6			320				18.3	8.7			
360		13.7	8.4	5.6	4	1.9		340			15.6	11.3	5.4			340					10.3			
380			9.7	6.5	4.7	2.2		360			18.3	13.2	6.3			360					12.1			
400				11.1	7.5	5.4	2.5	380				15.3	7.3			380					14			
420				12.6	8.5	6.1	2.9	400				17.6	8.4			400					16.1			
440				14.3	9.7	7	3.3	420				20.1	9.6			420					18.4			
460					10.9	7.9	3.7	440				10.9				440					20.9			
480						12.2	8.8	4.2	480				12.3				480					13.8		
500						13.7	9.8	4.7	500				15.4				500							

AmmonDrip 17, 2.2l/h, W.T 0.63mm, ID 15.6

Dripper spacing (cm)								
Lateral length(m)	20	30	40	50	60	70	100	
20	0.3	0.2	0.1	0.1	0.1	0.1	0.1	
40	1.9	0.8	0.4	0.3	0.2	0.2	0.1	
60	5.4	2.2	1.2	0.7	0.5	0.4	0.2	
80	11.5	4.7	2.5	1.5	1.1	0.8	0.4	
100	20.3	8.5	4.5	2.8	1.9	1.4	0.7	
120		13.7	7.3	4.5	3.1	2.2	1.1	
140		20.5	11	6.8	4.6	3.4	1.6	
160			15.8	9.7	6.7	4.8	2.3	
180				13.4	9.2	6.6	3.2	
200				17.8	12.1	8.8	4.2	
220					15.8	11.4	5.4	
240						20	14.5	6.9
260							18.5	8.6
280								10.5
300								12.7
320								15.2
340								18
360								21

AmmonDrip 17, 3.8l/h, W.T 0.63mm, ID 15.6

Dripper spacing (cm)							
Lateral length(m)	20	30	40	50	60	70	100
20	0.7	0.3	0.2	0.1	0.1	0.1	0.1
40	4.4	1.8	1	0.6	0.4	0.3	0.2
60	13.1	5.3	2.8	1.8	1.2	0.9	0.4
80		11.5	6.1	3.8	2.6	1.9	0.9
100		20.8	11.2	6.9	4.8	3.4	1.6
120			18.3	11.3	7.8	5.6	2.7
140				17.2	11.8	8.5	4.1
160					17	12.4	5.9
180						16.9	8.1
200							10.9
220							14.1
240							17.9

## THICK-WALLED PC FLAT DRIPLINE

**AmmonDrip 17mm - W.T 0.9-1.2mm****HEAD LOSS (m) IN RELATION TO LATERAL LENGTH (m), DRIPPER FLOW RATE AND SPACING (cm)**

AmmonDrip 17mm 0.5 l/h W.T 0.9-1.2 mm ID 14.4								AmmonDrip 17, 1.1l/h, W.T 0.9-1.2mm, ID 14.4								AmmonDrip 17, 1.6l/h, W.T 0.9-1.2mm, ID 14.4								AmmonDrip 17, 2.0l/h, W.T 0.9-1.2mm, ID 14.4									
Dripper spacing (cm)								Dripper spacing (cm)								Dripper spacing (cm)								Dripper spacing (cm)									
Lateral length(m)	20	30	40	50	60	70	100	Lateral length(m)	20	30	40	50	60	70	100	Lateral length(m)	20	30	40	50	60	70	100	Lateral length(m)	20	30	40	50	60	70	100		
40	0.2	0.1						40	0.7	0.3	0.1	0.1	0.1			40	1.3	0.5	0.3	0.2	0.1	0.1		40	1.8	0.8	0.4	0.3	0.2	0.2	0.1		
60	0.6	0.3	0.1	0.1	0.1			60	2	0.8	0.4	0.3	0.2	0.1	0.1	60	3.7	1.5	0.8	0.5	0.3	0.2	0.1	60	5.2	2.1	1.2	0.7	0.5	0.4	0.2		
80	1.4	0.5	0.3	0.2	0.1	0.1		80	4.3	1.7	0.9	0.6	0.4	0.3	0.1	80	8	3.3	1.7	1.1	0.7	0.5	0.3	80	11.1	4.6	2.5	1.6	1.1	0.8	0.4		
100	2.5	1	0.5	0.3	0.2	0.2	0.1	100	7.8	3.2	1.7	1	0.7	0.5	0.2	100	14.6	6	3.2	2	1.3	1	0.5	100	20.2	8.5	4.6	2.9	2	1.5	0.7		
120	4	1.6	0.8	0.5	0.4	0.3	0.1	120	12.7	5.2	2.7	1.7	1.2	0.8	0.4	120	23.7	9.8	5.2	3.2	2.2	1.6	0.8	120	25.5	13.8	7.5	4.7	3.2	2.4	1.2		
140	6	2.4	1.3	0.8	0.5	0.4	0.2	140	19.1	7.8	4.2	2.6	1.8	1.3	0.6	140	48	7.9	4.9	3.4	2.4	1.2		140	20.9	11.4	7.1	4.9	3.6	1.8			
160	8.5	3.5	1.8	1.1	0.8	0.6	0.3	160	11.2	6	3.7	2.5	1.8	0.9		160	21.2	11.4	7.1	4.9	3.5	1.7		160	25.6	16.3	10.2	7.1	5.2	2.5			
180	11.6	4.7	2.5	1.6	1.1	0.8	0.4	180	15.3	8.2	5.1	3.5	2.5	1.2		180	20.9	13.1	9	6	3.2			180	22.5	14.1	9.8	7.1	3.5				
200	15.4	6.3	3.3	2.1	1.4	1	0.5	200	20.4	11	6.8	4.7	3.4	1.6		200	47	11.6	8.5	4.1				200	25.7	18.8	13	9.5	4.6				
220	19.8	8.1	4.3	2.7	1.8	1.3	0.6	220	14.2	8.8	6	4.4	2.1			220	21.5	14.8	107	5.3				220	24.5	17	12.3	6					
240		10.2	5.5	3.4	2.3	1.7	0.8	240		18	11.2	7.7	5.6	2.7		240			18.5	13.4	6.6			240			21.5	15.7	7.7				
260		12.6	6.8	4.2	2.9	2.1	1	260		22.4	14	9.6	7	3.4		260			22.6	16.5	8			260			19.7	9.6					
280		15.4	8.3	5.1	3.5	2.5	1.2	280			17.1	11.7	8.5	4.1		280				19.9	9.7			280			24	11.7					
300		18.5	10	6.2	4.2	3.1	1.5	300			20.7	14.2	10.3	5		300				23.9	11.6			300				14.2					
320			11.9	7.4	5	3.7	1.8	320			24.6	16.9	12.3	6		320					13.8			320				17					
340			14	8.7	5.9	4.3	2.1	340				20	14.5	7.1		340					16.1			340				20.1					
360			16.3	10.2	6.9	5	2.4	360				23.3	17	8.3		360					18.7			360					21.6				
380			18.9	11.8	8.1	5.8	2.8	380					19.7	9.6		380					21.6			380					24.7				
400				13.5	9.2	6.7	3.3	400					22.8	11.1		400								400									
420				15.4	10.6	7.7	3.7	420						12.7		420								420									
440				17.5	12	8.7	4.2	440							14.4	440								440									
460				19.8	13.5	9.9	4.8	460							16.3	460								460									
480					15.2	11.1	5.4	480							18.4	480								480									
500						17	12.4	6	500							20.6	500								500								

AmmonDrip 17, 2.2l/h, W.T 0.9-1.2mm, ID 14.4								Dripper spacing (cm)										
Lateral length(m)	20	30	40	50	60	70	100	Lateral length(m)	20	30	40	50	60	70	100			
40	2.2	0.9	0.5	0.3	0.2	0.1	0.1	40										
60	6.3	2.6	1.4	0.9	0.6	0.4	0.2	60										
80	13.7	5.6	3	1.9	1.3	0.9	0.5	80										
100	24.9	10.3	5.5	3.4	2.3	1.7	0.8	100										
120		16.8	9	5.6	3.9	2.8	1.4	120										
140		25.4	13.7	8	5.9	4.3	2.1	140										
160			19.7	12.4	8.5	6.2	3	160										
180				17.1	11.8	8.6	4.2	180										
200					22.8	15.7	11.4	5.6	200									
220						20.4	14.9	7.3	220									
240							18.8	9.3	240									
260							23.6	11.6	260									
280								14.2	280									
300									17.2	300								
320									20.5	320								
340										24.3	340							

AmmonDrip 17mm, 3.8 l/h, W.T 0.9-1.2mm, ID 14.4								Dripper spacing (cm)							
Lateral length(m)	20	30	40	50	60	70	100	Lateral length(m)	20	30	40	50	60	70	100
20	1	0.4	0.2	0.1	0.1	0.1		20							
40	6.5	2.5	1.3	0.7	0.5	0.4	0.2	40							
60	19.2	7.4	3.8	2.2	1.5	1	0.5	60							
80		15.8	8.1	4.8	3.2	2.3	1.1	80							
100			14.7	8.8	5.9	4.2	1.9	100							
120			24.1	14.5	9.8	6.9	3.2	120							
140				22.1	14.8	10.4	4.9	140							
160					21.2	15.1	7	160							
180						20.9	9.7	180							
200							12.9	200							
220							16.8	220							
240							21.3	240							

# THICK-WALLED PC FLAT DRIPLINE **AmmonDrip 20mm**



## HEAD LOSS (m) IN RELATION TO LATERAL LENGTH (m), DRIPPER FLOW RATE AND SPACING (cm)

AmmonDrip-20mm 0.5 l/h W.T I.0-I.2 mm ID 17.7								AmmonDrip 20, 1.1l/h, W.T I.0-I.2mm, ID 17.7								AmmonDrip 20, 1.6l/h, W.T I.0-I.2mm, ID 17.7								AmmonDrip 20, 2.0l/h, W.T I.0-I.2mm, ID 17.7										
Dripper spacing (cm)								Dripper spacing (cm)								Dripper spacing (cm)								Dripper spacing (cm)										
Lateral length(m)	20	30	40	50	60	70	100	Lateral length(m)	20	30	40	50	60	70	100	Lateral length(m)	20	30	40	50	60	70	100	Lateral length(m)	20	30	40	50	60	70	100			
40	0.2	0.1	0.1					40	0.5	0.2	0.1	0.1	0.1	0.1	0.1	40	0.9	0.4	0.2	0.1	0.1	0.1	0.1	40	1.1	0.5	0.3	0.2	0.1	0.1	0.1			
60	0.6	0.3	0.1	0.1	0.1			60	1.3	0.6	0.3	0.2	0.1	0.1	0.1	60	2.1	1	0.5	0.3	0.2	0.2	0.1	60	2.8	1.3	0.7	0.5	0.4	0.3	0.1			
80	1.1	0.5	0.3	0.2	0.1	0.1		80	2.6	1.1	0.6	0.4	0.3	0.2	0.1	80	4.1	1.8	1	0.7	0.5	0.3	0.2	80	5.5	2.5	1.4	0.9	0.7	0.5	0.3			
100	1.8	0.8	0.4	0.3	0.2	0.1	0.1	100	4.3	1.9	1.1	0.7	0.5	0.3	0.2	100	6.9	3.1	1.7	1.1	0.8	0.6	0.3	100	9.2	4.2	2.4	1.5	1.1	0.8	0.4			
120	2.7	1.2	0.7	0.4	0.3	0.2	0.1	120	6.5	2.9	1.6	1	0.7	0.5	0.3	120	10.7	4.8	2.7	1.7	1.2	0.9	0.4	120	14.4	6.4	3.7	2.4	1.7	1.2	0.6			
140	3.8	1.7	0.9	0.6	0.4	0.3	0.1	140	9.2	4.1	2.3	1.5	1	0.8	0.4	140	15.4	6.9	3.9	2.5	1.8	1.3	0.7	140	20.7	9.3	5.3	3.4	2.4	1.8	0.9			
160	5.1	2.3	1.3	0.8	0.6	0.4	0.2	160	12.7	5.6	3.2	2	1.4	1.1	0.5	160	21.2	9.5	5.4	3.5	2.4	1.8	0.9	160	25.7	12.9	7.4	4.8	3.4	2.5	1.3			
180	6.7	2.9	1.7	1.1	0.7	0.5	0.3	180	16.7	7.4	4.2	2.7	1.9	1.4	0.7	180	24.6	12.6	7.2	4.6	3.3	2.4	1.2	180	27.3	9.9	6.4	4.5	3.3	2.3	1.7			
200	8.5	3.8	2.1	1.3	0.9	0.7	0.3	200	21.4	9.6	5.4	3.5	2.4	1.8	0.9	200	30.3	16.3	9.3	6	4.2	3.1	1.6	200	32.5	12.8	8.3	5.8	4.4	3.2	2.2			
220	10.6	4.7	2.6	1.7	1.2	0.9	0.4	220	24.1	12.1	6.8	4.4	3.1	2.3	1.1	220	40.7	20.7	11.7	7.6	5.3	4	2	220	45.6	16.3	10.5	7.5	5.5	4.8	2.8			
240	12.9	5.7	3.2	2.1	1.4	1.1	0.5	240	27.8	14.8	8.4	5.4	3.8	2.8	1.4	240	50.6	25.6	14.6	9.4	6.6	4.9	2.5	240	53.3	20.3	13.1	9.3	6.9	5.3	3.5			
260	15.6	6.9	3.9	2.5	1.7	1.3	0.6	260	31.5	18	10.2	6.6	4.6	3.4	1.7	260	75.8	21.8	17.8	11	8.1	6	3	260	78.8	24.8	16.1	11.3	8.5	6.3	3.9			
280	18.5	8.2	4.6	3	2.1	1.5	0.8	280	35.2	21.6	12.3	7.9	5.5	4.1	2.1	280	103.5	21.4	13.9	9.7	7.3	5.6	3.6	280	106.2	19.4	13.7	10.2	8.1	6.5	3.1			
300	9.6	5.4	3.5	2.4	1.8	0.9		300	38.9	25.6	14.5	9.4	6.6	4.9	2.4	300	117.5	25.5	16.5	11.6	8.6	6.3	4.3	300	122.2	23.2	16.4	12.2	9.1	7.1	4.1			
320	11.2	6.4	4.1	2.8	2.1	1		320	42.6	30.1	17.1	11	7.7	5.7	2.9	320	136.2	19.4	13.7	10.2	8.1	6.5	4.3	320	141.7	25.4	19.3	14.4	11.3	9.2	5.2			
340	13	7.3	4.7	3.3	2.4	1.2		340	46.3	34.9	19.9	12.8	9	6.7	3.3	340	150.8	22.7	16	11.9	6			340	155.5	22.4	16.8	12.8	10.5	8.5	5.5			
360	14.9	8.4	5.4	3.8	2.8	1.4		360	50.0	40.2	22.9	14.8	10.4	7.7	3.9	360	165.5	22.9	18.5	13.8	9.6			360	170.0	25.2	19.5	15.9	12.6	10.4	7.4			
380	16.9	9.6	6.1	4.3	3.2	1.6		380	53.7	44.9	26.6	16.9	11.9	8.8	4.4	380	181.2	21.3	15.8	10.8	7.8			380	186.0	22.5	16.3	12.2	9.1	7.0	4.8			
400	19.1	10.8	6.9	4.9	3.6	1.8		400	57.4	49.6	30.3	19.3	13.5	10	5	400	196.8	24.2	18	9.1				400	201.5	25.6	13	10.3	7.8	5.6	3.3			
420		12.2	7.8	5.5	4	2		420		61.1	53.0	21.8	15.3	11.4	5.7		420		211.2	21.8	20.5	10.3				420		216.0	14.7	14.7	10.3	7.8	5.6	3.3
440		13.6	8.8	6.1	4.5	2.3		440		64.8	56.4	24.5	17.2	12.8	6.4		440		221.9	23.1	23.1	11.7				440		226.7	16	11.9	6.1	4.8	3.5	2.3
460		15.2	9.8	6.8	5	2.5		460		68.5	60.1	26.2	19.3	14.3	7.2		460		231.6	25.9	25.9	13.1				460		236.4	16	11.9	6.1	4.8	3.5	2.3
480		16.8	10.8	7.6	5.6	2.8		480		72.2	61.9	28.9	21.5	15.9	8		480		241.3	21.8	21.8	14.7				480		246.1	16	11.9	6.1	4.8	3.5	2.3
500		18.6	12	8.4	6.2	3.1		500		75.9	64.7	33.9	23.9	17.7	8.9		500		250.2	23.1	23.1	16.3				500		254.9	16	11.9	6.1	4.8	3.5	2.3

AmmonDrip 20, 2.2l/h, W.T I.0-I.2mm, ID 17.7								AmmonDrip 20, 3.8 l/h, W.T I.0-I.2mm, ID 17.7							
Dripper spacing (cm)								Dripper spacing (cm)							
Lateral length(m)	20	30	40	50	60	70	100	Lateral length(m)	20	30	40	50	60	70	100
40	0.5	0.2	0.1	0.1	0.1	0.1		40	1.1	0.5	0.3	0.2	0.1	0.1	
60	2.6	1.2	0.7	0.4	0.3	0.2		60	2.8	1.3	0.7	0.5	0.4	0.3	
80	6.8	3.1	1.7	1.1	0.8	0.6		80	5.5	2.5	1.4	0.9	0.7	0.5	
100	13.5	6.1	3.5	2.2	1.6	1.2		100	9.2	4.2	2.4	1.5	1.1	0.8	
120	23.3	10.6	6	3.9	2.7	2		120	16.6	9.4	6.1	4.4	3.2	1.6	
140	44.4	13.9	9.1	6.4	4.7	2.4		140	24.4	13.9	9.1	6.4	4.7	2.4	
160	76.0	19.6	12.7	9	6.7	3.4		160	48.0	19.6	12.7	9	6.7	3.4	
180	117.7	26.5	17.2	12.2	9.1	6.1		180	72.7	26.5	17.2	12.2	9.1	6.1	
200	159.4	22.6	16	11.9	6			200	106.2	22.6	16	11.9	6.1		
220	192.1	20.5	15.3	10.8	7.8			220	141.7	20.5	15.3	10.8	7.8		
240	221.8	25.9	19.2	14.2	9.8			240	166.0	25.9	19.2	14.2	9.8		
260	241.5	23.7	21.1	17.4	12.1			260	186.7	23.7	21.1	17.4	12.1		
280	261.2	14.7	14.7	10.7	7.7			280	201.5	14.7	14.7	10.7	7.7		
300	281.0	17.7	17.7	13.4	9.8			300	221.8	17.7	17.7	13.4	9.8		
320	301.7	21.1	21.1	15.3	11.6			320	241.5	21.1	21.1	15.3	11.6		
340	321.4	23.1	23.1	17.4	12.1			340	261.2	23.1	23.1	17.4	12.1		

## THICK-WALLED PC FLAT DRIPLINE

**AmmonDrip 23mm****HEAD LOSS (m) IN RELATION TO LATERAL LENGTH (m), DRIPPER FLOW RATE AND SPACING (cm)**

Ammon-23mm ,0.5 l/h W.T 1.0 mm ID 20.8								AmmonDrip 23, 1.1 l/h, W.T 1.00mm, ID 20.8								AmmonDrip 23 1.6l/h, W.T 1.00mm, ID 20.8								AmmonDrip 23, 2.0l/h, W.T 1.00mm, ID 20.8									
Dripper spacing (cm)								Dripper spacing (cm)								Dripper spacing (cm)								Dripper spacing (cm)									
Lateral length(m)	20	30	40	50	60	70	100	Lateral length(m)	20	30	40	50	60	70	100	Lateral length(m)	20	30	40	50	60	70	100	Lateral length(m)	20	30	40	50	60	70	100		
40	0.1							40	0.2	0.1						40	0.2	0.1	0.1					40	0.3	0.2	0.1	0.1					
60	0.2	0.1						60	0.4	0.2	0.1	0.1				60	0.6	0.3	0.2	0.1	0.1	0.1		60	0.8	0.4	0.3	0.2	0.1	0.1			
80	0.3	0.1	0.1	0.1				80	0.7	0.3	0.2	0.1	0.1	0.1		80	1.2	0.5	0.3	0.2	0.1	0.1	0.1	80	1.6	0.8	0.5	0.3	0.2	0.2	0.1		
100	0.5	0.2	0.1	0.1	0.1			100	1.2	0.6	0.3	0.2	0.1	0.1	0.1	100	2	0.9	0.5	0.4	0.3	0.2	0.1	100	2.8	1.3	0.8	0.5	0.4	0.3	0.2		
120	0.7	0.3	0.2	0.1	0.1	0.1		120	1.8	0.9	0.5	0.3	0.2	0.2	0.1	120	3.1	1.5	0.8	0.6	0.4	0.3	0.2	120	4.3	2	1.2	0.8	0.6	0.5	0.3		
140	1	0.5	0.3	0.2	0.1	0.1		140	2.7	1.2	0.7	0.5	0.3	0.2	0.1	140	4.6	2.1	1.2	0.8	0.6	0.4	0.2	140	6.4	3	1.8	1.2	0.8	0.7	0.4		
160	1.4	0.7	0.4	0.2	0.2	0.1	0.1	160	3.7	1.7	1	0.7	0.5	0.3	0.2	160	6.4	3	1.7	1.1	0.8	0.6	0.3	160	9	4.2	2.5	1.6	1.2	0.9	0.5		
180	1.9	0.9	0.5	0.3	0.2	0.2	0.1	180	4.9	2.3	1.3	0.9	0.6	0.5	0.2	180	8.7	4	2.3	1.5	1.1	0.8	0.4	180	12.1	5.7	3.3	2.2	1.6	1.2	0.6		
200	2.4	1.1	0.6	0.4	0.3	0.2	0.1	200	6.4	3	1.7	1.1	0.8	0.6	0.3	200	11.3	5.3	3.1	2	1.4	1.1	0.6	200	15.9	7.5	4.4	2.9	2.1	1.6	0.8		
220	3	1.4	0.8	0.5	0.4	0.3	0.1	220	8.1	3.8	2.2	1.4	1	0.8	0.4	220	14.4	6.7	3.9	2.6	1.8	1.4	0.7	220	20.4	9.5	5.6	3.7	2.7	2	1		
240	3.7	1.7	1	0.6	0.5	0.3	0.2	240	10.1	4.7	2.7	1.8	1.3	1	0.5	240	18.1	8.4	4.9	3.2	2.3	1.7	0.9	240	25.3	12	7	4.6	3.3	2.5	1.3		
260	4.5	2.1	1.2	0.8	0.6	0.4	0.2	260	12.3	5.7	3.3	2.2	1.6	1.2	0.6	260	22.2	10.4	6	4	2.8	2.1	1.1	260	14.8	8.7	5.7	4.1	3.1	1.6			
280	5.3	2.5	1.4	0.9	0.7	0.5	0.3	280	14.9	7	4	2.7	1.9	1.4	0.7	280	12.6	7.3	4.8	3.4	2.6	1.3		280	18	10.6	7	5	3.7	1.9			
300	6.3	2.9	1.7	1.1	0.8	0.6	0.3	300	17.8	8.3	4.8	3.2	2.3	1.7	0.9	300	15.1	8.8	5.8	4.1	3.1	1.6		300	21.7	12.7	8.4	6	4.5	2.3			
320	7.4	3.4	2	1.3	0.9	0.7	0.4	320	21	9.8	5.7	3.7	2.7	2	1	320	17.9	10.5	6.9	4.9	3.7	1.9		320	25.5	15.5	9.9	7.1	5.3	2.8			
340	8.5	4	2.3	1.5	1.1	0.8	0.4	340	24.5	11.5	6.7	4.4	3.1	2.3	1.2	340	21	12.3	8.1	5.8	4.3	2.2		340	17.7	11.7	8.3	6.3	3.2				
360	9.8	4.6	2.7	1.7	1.2	0.9	0.5	360		13.3	7.8	5.1	3.6	2.7	1.4	360	24.4	14.3	9.4	6.7	5	2.6		360	20.7	13.6	9.7	7.3	3.8				
380	11.2	5.2	3	2	1.4	1.1	0.5	380		15.3	8.9	5.9	4.2	3.1	1.6	380	16.5	10.9	7.7	5.8	3			380	23.3	15.8	11.2	8.5	4.4				
400	12.8	5.9	3.5	2.3	1.6	1.2	0.6	400		17.5	10.2	6.7	4.8	3.6	1.8	400	18.9	12.5	8.9	6.7	3.4			400	25.4	18.1	12.9	9.7	5				
420	14.4	6.7	3.9	2.6	1.8	1.4	0.7	420		19.8	11.6	7.6	5.4	4.1	2.1	420	21.6	14.2	10.1	7.6	3.9			420	20.7	14.8	11.1	5.7					
440	16.2	7.5	4.4	2.9	2	1.5	0.8	440		22.4	13.1	8.6	6.1	4.6	2.4	440	24.5	16.1	11.5	8.6	4.4			440	23.4	16.7	12.6	6.5					
460	18.1	8.4	4.9	3.2	2.3	1.7	0.9	460		25.22	14.7	9.7	6.9	5.2	2.7	460		18.1	12.9	9.7	5				460	25.1	18.8	14.2	7.3				
480		9.4	5.5	3.6	2.5	1.9	1	480			16.5	10.8	7.7	5.8	3	480			20.3	14.5	10.9	5.6		480			21.2	15.9	8.2				
500			10.4	6.1	4	2.8	2.1	500				18.4	12.1	8.6	6.5	3.3	500				22.7	16.2	12.2	6.3		500			23.7	17.8	9.2		



AmmonDrip 23 2.2l/h, W.T 1.00mm, ID 20.8

Dripper spacing (cm)							
Lateral length(m)	20	30	40	50	60	70	100
40	0.4	0.2	0.1	0.1			
60	0.9	0.4	0.3	0.2	0.1	0.1	
80	1.8	0.9	0.5	0.3	0.2	0.2	0.1
100	3.2	1.5	0.9	0.6	0.4	0.3	0.2
120	5	2.4	1.4	0.9	0.6	0.5	0.3
140	7.4	3.5	2	1.3	1	0.7	0.4
160	10.5	4.9	2.9	1.9	1.3	1	0.5
180	14.2	6.6	3.9	2.5	1.8	1.4	0.7
200	18.7	8.8	5.1	3.4	2.4	1.8	0.9
220	24	11.2	6.5	4.3	3.1	2.3	1.2
240	14.1	8.2	5.4	3.9	2.9	1.5	
260		17.5	10.2	6.7	4.8	3.6	1.9
280		21.3	12.4	8.2	5.8	4.4	2.3
300		25.6	14.9	9.8	7	5.3	2.7
320			17.8	11.7	8.4	6.3	3.2
340			21	13.8	9.8	7.4	3.8
360			24.5	16.1	11.4	8.6	4.5
380				18.6	13.3	9.9	5.2
400				21.4	15.2	11.5	5.9
420				24.4	17.4	13.1	6.8
440					19.8	14.8	7.7
460					22.3	16.8	8.7
480					25	18.8	9.7
500						21.1	10.9

AmmonDrip 23 3.8l/h, W.T 1.00mm, ID 20.8

Dripper spacing (cm)							
Lateral length(m)	20	30	40	50	60	70	100
20	0.2	0.1					
40	0.7	0.4	0.2	0.1	0.1		
60	2	1	0.6	0.4	0.3	0.2	0.1
80	4.2	2	1.1	0.7	0.5	0.4	
100	7.4	3.5	2	1.3	0.9	0.7	0.4
120	11.9	5.6	3.2	2.1	1.5	1.2	0.6
140	17.8	8.4	4.9	3.2	2.3	1.7	0.9
160	25.5	11.9	7	4.6	3.3	2.5	1.3
180		16.3	9.5	6.3	4.5	3.4	1.8
200		21.7	12.6	8.3	6	4.5	2.3
220			16.4	10.8	7.7	5.8	3
240				20.7	13.7	9.8	7.3
260					17	12.1	9.1
280						20.8	